

# EVO 2T

## Two-Stroke Motorcycle Oil

**EVO 2T** is a two-stroke motorcycle oil specially formulated for the demands of tricycles to help achieve peak machine performance. It balances components to allow thorough mixing with fuels of 30:1 to 40:1 ratio.

### Product Applications:

- Motorcycles, scooters, lawn mowers, small tractors, and other portable equipment powered with two-stroke gasoline engines

### Performance Benefits:

- Excellent protection from rust, corrosion, and wear
- Prevents piston scuffing and ring sticking
- Low smoke and scented

### Performance Level:

- Meets:** JASO FB; API TA

TYPICAL SPECIFICATIONS:		
Test Parameters	Test Method	Results
<b>SAE Viscosity Grade</b>		<b>30</b>
Kinematic Viscosity @ 100°C, cSt	ASTM D7042	10.8
Kinematic Viscosity @ 40°C, cSt	ASTM D7042	95.8
Viscosity Index	ASTM D2270	96
Flash Point, °C (min)	ASTM D3828	220
Density @ 15°C, kg/L	ASTM D4052	0.877
ASTM Color	Visual	Amber Yellow

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.

## CHEMICAL ALLOY CORPORATION