

FORK OIL

High Performance Suspension Fluid

FORK OIL is a high performance suspension fluid specially formulated from highly refined base stocks blended with superior performance-enhancing additives. It is designed to meet the lubrication requirements of motorcycle forks, dampers and suspensions and engineered to provide protection against wear and corrosion in the fork.

Product Applications:

Motorcycle front forks, upside down forks, telescopic forks, rear damper units, and hydraulic shock absorbers

Performance Benefits:

- Stay-in-grade viscosity properties
- Inhibits corrosion and formation of rust on fork
- High oxidation stability that maintains performance level for a longer period of oil drain intervals
- Good compatibility with elastomers used in motorcycle forks and shock absorbers

TYPICAL SPECIFICATIONS:		
Test Parameters	Test Method	Results
SAE Viscosity Grade		5W
Kinematic Viscosity @ 100°C, cSt	ASTM D7042	3.8
Kinematic Viscosity @ 40°C, cSt	ASTM D7042	17
Viscosity Index	ASTM D2270	114
Flash Point, °C (min)	ASTM D3828	170
Density @ 15°C, kg/L	ASTM D4052	0.860
ASTM Color	Visual	Clear Yellow

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.