

## **POWER PLUS SYNTHETIC**Fully Synthetic Gasoline Engine Oil

**POWER PLUS SYNTHETIC** is a fully synthetic multi-grade gasoline engine oil formulated from the highest quality synthetic base stocks and enhanced with the most advanced additive technology for ultimate performance in meeting the latest industry requirements.

## **Product Applications:**

Recommended for luxury and high-performance vehicles, SUVs, vans, and high-speed light-duty diesel engines

## **Performance Benefits:**

- Outstanding thermal and oxidation stability that reduces high temperature deposits
- Improved shear stability and breakdown resistance that provide sufficient lubricating films to protect engine parts against metal to metal contact
- Enhanced detergent system for ultimate cleaning performance
- ₹ Increased operating efficiency obtained from longer oil drain interval
- Easier engine start-up due to its exceptional low-temperature pump ability

## **Performance Level:**

Meets: API SN, SM, SJ/CF; ILSAC GF-5; GM dexos1™; ACEA C3

| TYPICAL SPECIFICATIONS:          |             |         |
|----------------------------------|-------------|---------|
| Test Parameters                  | Test Method | Results |
| SAE Viscosity Grade              |             | 5W-40   |
| Kinematic Viscosity @ 100°C, cSt | ASTM D7042  | 14.0    |
| Kinematic Viscosity @ 40°C, cSt  | ASTM D7042  | 86.2    |
| Viscosity Index                  | ASTM D2270  | 168     |
| Flash Point, °C (min)            | ASTM D3828  | 205     |
| Pour Point, °C (max)             | ASTM D97    | -35     |
| TBN, mg KOH/g sample             | ASTM D4739  | 7.88    |
| Density @ 15°C, kg/L             | ASTM D4052  | 0.865   |
| ASTM Color                       | ASTM D1500  | L2.0    |

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.