

# EVO 4T PRIME

## Multi-Grade Four-Stroke Motorcycle Oil

**EVO 4T PRIME** is a modern, high technology, premium multi-grade four-stroke motorcycle oil formulated from high viscosity index mineral oils blended with additives. It provides smooth gear change operations in a wide range of conditions and excellent protection and superior performance in all working conditions.

### Product Applications:

- Standard air-cooled and water-cooled four-stroke motorcycle engines requiring API SJ and lower classifications

### Performance Benefits:

- Offers excellent engine protection against mechanical breakdown, both for the first ignition start-up and in high temperature operating conditions
- Superior resistance to oil thickening and oxidation
- Enhanced engine protection against wear
- Effective protection from rust and corrosion
- Superior resistance to shearing due to stay-in-grade viscosity

### Performance Level:

- Meets: API SJ

TYPICAL SPECIFICATIONS:		
Test Parameters	Test Method	Results
SAE Viscosity Grade		20W-50
Kinematic Viscosity @ 100°C, cSt	ASTM D7042	18.0
Kinematic Viscosity @ 40°C, cSt	ASTM D7042	160
Viscosity Index	ASTM D2270	125
Flash Point, °C (min)	ASTM D3828	230
TBN, mg KOH/g sample	ASTM D4739	5.1
Density @ 15°C, kg/L	ASTM D4052	0.890
ASTM Color	Visual	Dyed Red

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.

## CHEMICAL ALLOY CORPORATION