

POWER PLUS SYNTHETIC FORTIFIED

Synthetic Blend Gasoline Engine Oil

POWER PLUS SYNTHETIC FORTIFIED is a synthetic blend of multi-grade gasoline engine oil formulated with the highest quality of synthetic and severely hydrocracked base stock and advanced additive technology that provides longer protection and supreme performance for modern gasoline-fueled engines. It is designed primarily to help extend engine life while providing long drain capability.

Product Applications:

- Recommended for modern gasoline vehicles
- Also suitable for well maintained heavy-duty diesel engines

Performance Benefits:

- Good thermal and oxidation stability
- Reduces formation of sludge and varnish deposits
- ₹ Improves oil film strength and breakdown resistance
- ₹ Lowers oil vaporization and consumption at extreme temperatures
- Reduces fuel consumption and extend the oil drain interval

Performance Level:

■ Meets: API SN/CF; ILSAC GF-4; ACEA A3/B4

| TYPICAL SPECIFICATIONS: | | |
|----------------------------------|-------------|---------|
| Test Parameters | Test Method | Results |
| SAE Viscosity Grade | | 10W-40 |
| Kinematic Viscosity @ 100°C, cSt | ASTM D7042 | 14.39 |
| Kinematic Viscosity @ 40°C, cSt | ASTM D7042 | 95.5 |
| Viscosity Index | ASTM D2270 | 155 |
| Flash Point, °C (min) | ASTM D3828 | 210 |
| Pour Point, °C (max) | ASTM D97 | -33 |
| TBN, mg KOH/g sample | ASTM D4739 | 7.6 |
| Density @ 15°C, kg/L | ASTM D4052 | 0.901 |
| ASTM Color | ASTM D1500 | L2.5 |

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.