




EP GREASE 1 & 2



Extreme Pressure Grease

EP GREASE 1 & 2 are superior, premium quality, extreme pressure greases in lithium thickener soap formulated from high viscosity, highly refined base stocks blended with sulfur-phosphorus base extreme pressure additives and rust and oxidation inhibitors. They provide superior protection in boundary lubrication regions of bearing elements.

Product Applications:

-  All types of rolling element bearings, pins, bushings, and many other applications in marine, pulp and paper, agricultural, industrial, construction, earth moving, and mining industrial equipment
-  Multipurpose automotive grease for general purpose applications
-  High load and high pressure applications

Performance Benefits:

-  Protect metals against surface fatigue due to prevalent shock loading
-  Provide continuous protection against metal-to-metal contact of bearing surfaces

TYPICAL SPECIFICATIONS:				
Test Parameters		Test Method	Results	
NLGI Number			No. 1	No. 2
Soap Type			Lithium	Lithium
Base Oil			Mineral	Mineral
Color	Visual		Yellow	Yellow
Kinematic Viscosity @ 40°C, cSt	ASTM D7042		200	200
Kinematic Viscosity @ 100°C, cSt	ASTM D7042		16.8	17
Dropping Point, °C	IP 396		180	181
Penetration, worked 60 strokes			325	280

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.