

EVO 4T POWERSYN

SYNTHETIC BLEND MOTORCYCLE OIL

EVO 4T POWERSYN is a synthetic blend multi-grade motorcycle oil suitable for all four-stroke motorcycles in a wide range condition. It is formulated from highest quality of synthetic and severely hydrocracked base stock with advanced additive technology that provides longer protection and superior performance.

Product Applications:

Standard air-cooled and water cooled four-stroke motorcycle engines requiring API SN and lower classifications

Performance Benefits:

- Good thermal, shear and oxidation stability
- Reduces formation of sludge and varnish deposits
- Improves oil film strength and breakdown resistance
- Lowers oil vaporization and consumption at extreme temperatures
- Excellent corrosion protection

Performance Level:

Meets: API SN

Typical Specifications:		
Test Parameters	Test Method	Results
SAE Viscosity Grade		10W-40
Kinematic Viscosity @ 100°C, cSt	ASTM D7042	14.47
Kinematic Viscosity @ 40°C, cSt	ASTM D7042	99.23
Viscosity Index	ASTM D2270	151
Flash Point, °C (min)	ASTM D3828	234
Pour Point, °C (min)	ASTM D5950-14	-42
TBN, mg KOH /g sample	ASTM D4739	7.0
Density @ 15°C, kg/L	ASTM D4052	0.8603
ASTM Color	ASTM D1500	2.5

LA.REF.006-21 Rev.000

Nov. 2, 2022

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.